


# Single-Axis Positioning Control MA90/MA91

Single-axis control for direct positioning via required-value input. Its memory enables the storage of 99 required values. Required and actual values can be read simultaneously from the two-digit display. Various drives can be positioned via switching outputs.

## Features:

- easy to use (10-key pad, programming menus)
- input cards for rotary encoders and magnetic sensors (incremental and absolute)
- optional RS232 or RS485 interface
- position control via tolerance window, pre-switching point and loop positioning
- set positioning, piece counter (MA91)



## Pin outs

PIN	Powerpack unit+interface RS232	RS485
1	+24 V operating voltage	+24 V operating voltage
2	+24 V operating voltage	+24 V oper. volt.
3	0 V GND	0 V GND
4	0 V GND	0 V GND
5	n.c.	TXD
6	n.c.	RXD
7	n.c.	GND interface
8	n.c.	n.c.
9	n.c.	n.c.

PIN	PP, OC	LD5, LD	NPN	PNP	SSI
1	+ Ub encoder power supply	+ Ub encoder power supply	IN 1 start of positioning	IN 1 start of positioning	+ Ub enc. power supply
2	A signal	A signal	IN 2 stop of positioning	IN 2 stop of positioning	clock+
3	n.c.	/A signal	IN 3 jog mode left-h. motion	IN 3 jog mode left-h. motion	clock-
4	B signal	B signal	IN 4 jog mode right-h. motion	IN 4 jog mode right-h. motion	data+
5	n.c.	/B signal	GND	GND	data-
6	index signal	index signal	Out 1 right-h. motor motion	Out 1 right-h. motor motion	GND, screen enc. supply
7	n.c.	/index signal	Out 2 left-h. motor motion	Out 2 left-h. motor motion	+24 V
8	GND	GND	Out 3 fast motor motion	Out 3 fast motor motion	CAL
9	RFS	RFS	Out 4 position reached	Out 4 position reached	GND
10	+24 V	+24 V	GND	U in	SE

MA90 panel-mount housing (EG), mounting example

Feature	MA90	MA91	Technical data	Additional information
Power supply			24 V DC ±20 %	
Display			text display LCD, 2 x 16 characters	backlit
Functional card I/O			4 transistor outputs 30 V DC (100 mA) for motor control 4 opto-coupler inputs, 15 to 30 V DC	galvanically isolated
Input card incremental			PP/OC, LD5, LD24	
counting frequency			25 kHz, optional 150 kHz	
encoder power supply			24 V DC (200 mA), 5 V DC (200 mA)	
Input card absolute			SSI	synchronous serial interface
bit width			max. 25 bit	
encoder power supply			24 V DC (200 mA)	
Input card MLI			SIKO magnetic sensor, type MS500	
Input card MLA			SIKO magnetic sensor, type MSA	
Data and actual value memory			EEPROM min. 25 years	
Memory			up to 99 position values	(required values)
Keyboard			membrane keys with key force	
Electrical connection			edge clip, mini-DIN connector for MS500	
Operating temperature			0 ... +50 °C, no condensation	
Housing			EG: plastic TG: aluminium profile	plugboard cut-out 92 x 92 mm, DIN 43700
Weight			approx. 0.37 kg EG design	

**Ordering data**

Design	EG	EG	A	panel-mount housing	standard*
	TG	TG	A	bench-top housing	
Operating voltage	4	4	B	24 V DC ±20 %	standard
	1	1	B	230 V DC +6/-10 %	TG design
Input/output 1	X	X	C	without	standard
	I/O,NPN	I/O,NPN		grounding	
	I/O,PNP	I/O,PNP		positive switching	
input 2	X	X	D	without	standard
	PP/OC	PP/OC		push-pull/ open collector 24 V DC	
	LD/5	LD/5		RS422/ 5 V	
	LD/24	LD/24		RS422/ 24 V	
	SSI	SSI		synchronous serial interface	
	MLI			magnetic measuring system incremental	
	MLA			magnetic measuring system absolute	
input 3	...	...	E	see input 2	
input 4	X	X	F	without	standard
	MLI			magnetic measuring system incremental	
	MLA			magnetic measuring system absolute	
Interface/protocol	X	X	C	without	standard
	S1/00	S1/00		RS232/ standard	
	S3/00	S3/00		RS485/ standard	

\* All mating connectors are included in the delivery.

Your order:

MA90/91 - A - B - C - D - E - F - G